

# HYDRAULIC MOTOR REELS



## 1" TO 3" HOSE HYDRAULIC MOTOR DRIVEN

### Standard Equipment

- 500 psi
- Ball bearings both sides
- Extra heavy duty on reels for 3" hose
- Aluminum flow path for 3" hose
- Powder coat finish

### Optional Equipment

- Higher pressure for 1" hose
- Brass swivel joints

**American Reels hydraulic driven motor reels are designed to simplify and streamline the process of storing and retracting hoses in industrial and commercial settings.** These hose reels are powered by hydraulic motors, which provide reliable and efficient performance in a range of applications.

One of the key benefits of our hydraulic driven motor hose reels is the ability to easily handle larger hoses. With the hydraulic motor providing ample power, these reels can quickly and easily retract and deploy hoses of varying sizes and lengths, saving time and effort for operators.

In addition to their powerful performance, our hydraulic driven motor hose reels are also durable and long-lasting, thanks to their robust construction and high-quality components. They are designed to withstand heavy use and harsh environments, making them ideal for use in industries such as construction, mining, and agriculture.


**RUGGED BY DESIGN**

775.246.1000 | [WWW.AMERICANREELS.COM](http://WWW.AMERICANREELS.COM)

# HYDRAULIC MOTOR REELS 1" TO 3" HOSE

When ordering - Please supply the following information.

- 1 - Model number of reel
- 2 - Right or left hand inlet
- 3 - Top or bottom wind
- 4 - Straight or elbow inlet
- 5 - Product to be handled



Model	Hose		Dimensions in Inches						
	I.D.	Length	A	B	C	D	E	F	G
H1115-20-10	1"	50'	20	21 1/2	15	11	27	20	22
H1110-22-10	1"	50'	22	23 1/2	10	11	22	20	17
H1108-25-10	1"	50'	25	26 1/2	8	11	20	20	15
H1125-20-10	1"	100'	20	21 1/2	25	11	37	20	32
H1115-22-10	1"	100'	22	23 1/2	15	11	27	20	22
H1112-25-10	1"	100'	25	26 1/2	12	11	24	20	19
H1120-22-10	1"	150'	22	23 1/2	20	11	32	20	27
H1115-25-10	1"	150'	25	26 1/2	15	11	27	20	22
H1110-28-10	1"	150'	28	29 1/2	10	11	22	20	17
H1125-22-10	1"	200'	22	23 1/2	25	11	37	20	32
H1120-25-10	1"	200'	25	26 1/2	20	11	22	20	27
H1115-28-10	1"	200'	28	29 1/2	15	11	27	20	22
H1112-22-12	1 1/4"	50'	22	23 1/2	12	11	24	20	19
H1110-25-12	1 1/4"	50'	25	26 1/2	10	11	22	20	17
H1120-22-12	1 1/4"	100'	22	23 1/2	20	11	32	20	27
H1115-25-12	1 1/4"	100'	25	26 1/2	15	11	27	20	22
H1125-22-12	1 1/4"	150'	22	23 1/2	25	11	20	20	32
H1120-28-12	1 1/4"	150'	28	29 1/2	20	11	20	20	27
H1115-22-15	1 1/2"	50'	22	23 1/2	15	11	27	20	22
H1112-25-15	1 1/2"	50'	25	26 1/2	12	11	24	20	19
H1110-28-15	1 1/2"	50'	28	29 1/2	10	11	22	20	17
H1130-22-15	1 1/2"	100'	22	23 1/2	30	11	42	20	37
H1125-25-15	1 1/2"	100'	25	26 1/2	25	11	37	20	32
H1120-28-15	1 1/2"	100'	28	29 1/2	20	11	32	20	27
H1130-25-15	1 1/2"	150'	25	26 1/2	30	11	42	20	37
H1125-28-15	1 1/2"	150'	28	29 1/2	25	11	37	20	32
H1135-25-15	1 1/2"	200'	25	26 1/2	35	11	47	20	42
H1130-28-15	1 1/2"	200'	28	29 1/2	30	11	42	20	37
H1615-28-20	2"	50'	28	30	15	16	27 1/2	25	22 1/2
H1610-36-20	2"	50'	36	38	10	16	22 1/2	25	17 1/2
H1630-28-20	2"	100'	28	30	30	16	42 1/2	25	37 1/2
H1620-36-20	2"	100'	36	38	20	16	32 1/2	25	27 1/2
H2020-36-30	3"	50'	36	38	20	20	32 1/2	25	27 1/2
H2010-44-30	3"	50'	44	46	10	20	22 1/2	32	17 1/2
H2015-44-30	3"	100'	44	46	15	20	27 1/2	32	22 1/2

\* For solid rims deduct 1" to E & G dimensions.  
Specifications are subject to change without notice.



American Reels is a brand of  
United Equipment Accessories, Inc.

15 Airpark Vista Blvd • Dayton, NV 89403 • 775-246-1000  
www.americanreels.com • sales@americanreels.com

Copyright © 2023 United Equipment Accessories, Inc.